

REVISION HISTORY OF: 020-000708-01			
REV	DESCRIPTION OF CHANGE	BY	REV DATE
01	INITIAL RELEASE	JL	01/29/2014

LCD PANEL FHD651-P
(151-001102-XX)

ISO FRONT VIEW

TOP VIEW

8.4 [.33]
MIN CLEARANCE
FOR VENTILATION
(BACK OF PANEL
TO WALL)

DO NOT OBSTRUCT
AIRFLOW

WALL

43.1 [1.70]
BEZEL WIDTH

DO NOT
OBSTRUCT
AIRFLOW

803.7 [31.64]
ACTIVE DISPLAY

1639.1 [64.53]
ACTIVE DISPLAY

DO NOT
REST PANEL
ON ANY CORNER

CONNECTOR
LOCATIONS
ON THIS SIDE

OSD BUTTON
DISPLAY

4X M8 VESA
MOUNTING HOLES

400.0 [15.75]

231.9 [9.13]

DO NOT OBSTRUCT
AIR FLOW IN ANY
PERFORATED PANEL
LOCATION

FRONT VIEW

LEFT VIEW

RIGHT VIEW

BACK VIEW

BOTTOM VIEW

DO NOT OBSTRUCT
AIRFLOW

GENERAL NOTES:

- NET WEIGHT: 55KG
GROSS WEIGHT: 70KG
- LCD DISPLAY (HD 1920X1080), ASPECT RATIO 16:9
- OPERATING TEMPERATURE: 5°C TO 40°C / 90% RH
STORAGE TEMPERATURE: -20°C TO 60°C
- POWER REQUIREMENTS: AC100-240V(WORLDWIDE), MAX 3A, 50/60Hz
- MAX POWER CONSUMPTION: 223W
TYPICAL POWER CONSUMPTION: 160W
- PANELS ARE INTENDED FOR STAND ALONE INSTALLATIONS ONLY.
FOR RECESSED/ALCOVE INSTALLATIONS CONTACT A CHRISTIE
REPRESENTATIVE FOR VENTILATION REQUIREMENTS

UNITS		MILLIMETRES		DRAWN BY		J. LUTCH		CHRISTIE DIGITAL SYSTEMS USA, INC. CHRISTIE DIGITAL SYSTEMS CANADA, INC.	
INCHES		MILLIMETRES		DRAWN DATE		01/29/2014		DWG Line FHD651-P	
UNLESS OTHERWISE SPECIFIED		INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M-1994		APPROVED BY		V. VARSHAMAN			
TOLERANCES APPLY AS SHOWN BELOW				APPROVAL DATE		01/31/2014			
DECIMAL PLACES		INCHES		MILLIMETRES		PROPRIETARY		PART DESCRIPTION	
.XXX		± .003		± 1.6		NOT TO BE DISCLOSED OR REPRODUCED IN ANY MANNER WITHOUT THE EXPRESS WRITTEN PERMISSION OF CHRISTIE		020-000708-01	
.XX		± .125		± 3.1					
.X		± .250		± 6.3					
ANGULAR DIMENSIONS		°		°		THIRD ANGLE PROJECTION		SHEET 1 OF 1	
XX°		± 1.0°		± 0.5°		SCALE 1:4		MASS LBS [KG]	
XX.X°		± 0.5°		± 0.2°					